



1-082SL Quarter-Turn Pr30 L18 SNAP-LINE



TRENTA, for cutout 30x30, length 18, for inserts, tool-less installation

Benefits:

- ▶ Elegant, flush Quarter-turn for Snap-in installation into cutout 30x30mm.
- ▶ RH and LH application.
- ▶ The Quarter-turn can be snapped-in as a completely pre-assembled unit.
- ▶ To guarantee a correct positional installation, the cutouts can have indentations.
- ▶ **Attention: H-dimension not less than 14mm (0.551)!**
- ▶ **Water- and dust-tight according to IP65**
DIN EN 60529 by: O-ring 200-1001 and 839-3770.00-03620.
- ▶ **Grounding by:** Grounding clip 200-1105.93-00000.

Material:

- ▶ **Housing:** zinc die, black
- ▶ **Snap wedges:** sintered steel
- ▶ **Clip:** spring steel



Quarter-turn TRENTA

Part Number	Housing length	Material	Surface	Grounding type	Installation type	Quantity SNAP wedges	Clamping range
406-9001.00-00015	L18	zinc die	black	Grounding clip	tool-less	4, for H.D. applications	0.8 - 1.5
406-9001.00-00020	L18	zinc die	black	Grounding clip	tool-less	4, for H.D. applications	1.3 - 2.0
406-9001.00-00022	L18	zinc die	black	Grounding clip	tool-less	4, for H.D. applications	1.5 - 2.2
406-9002.00-00015	L18	zinc die	black	Grounding clip	tool-less	2, for light applications	0.8 - 1.5
406-9002.00-00020	L18	zinc die	black	Grounding clip	tool-less	2, for light applications	1.3 - 2.0
406-9002.00-00022	L18	zinc die	black	Grounding clip	tool-less	2, for light applications	1.5 - 2.2

Complementary Products:

1-095	Insert PA Pr20.1
1-101	Inserts Pr20.1
7-082	Insert stainless steel Pr20.1
1-095	Cams PA
1-102	Cams L35/45
1-262	Cam with or without ramp
7-105	Cams L35/45
2-151	2-, 3- and 4-Point Cam Adapter
200-1105.93-00000	Grounding clip
200-1001.00-00000	O-ring 12 x 2.0mm
839-3770.00-03620	O-ring 36 x 2.0mm
292-0306.80-02530	Tool for uninstallation

