



# 1-083 Quarter-Turn Pr20.1 L12



Nicely shaped Quarter-turn with 12mm (0.472) housing

### Benefits:

- ▶ RH or LH application.
- ▶ Please configure the Quarter-turn with insert and cam.
- ▶ On request parts can be assembled.
- ▶ The Quarter-turn can be screwed into the cutout with the pre-assembled cam.
- ▶ Grounding is possible with use of a grounding nut.
- ▶ IP65 according to DIN EN 60529 by using sealing kit 209-9002.

### Material:

- ▶ **Housing and inserts:** zinc die, chrome plated or black
- ▶ **Cams and nut:** steel, zinc plated
- ▶ **Grounding nut:** zinc die, untreated

H-dimension ≥6 mm



## Housing

	Part Number	Housing length	Door-thickness	Material	Surface	Grounding type	Installation type	Version
a)	100-9044.00-00000	L12	max.3mm	zinc die	chrome plated		screw-on	chrome plated
a)	100-9045.00-00000	L12	max.3mm	zinc die	chrome plated	Grounding nut	screw-on	chrome plated
a)	100-9046.00-00000	L12	max.3mm	zinc die	black		screw-on	black
a)	100-9047.00-00000	L12	max.3mm	zinc die	black	Grounding nut	screw-on	black

### Complementary Products:

	1-083	Insert Pr20.1
b)	1-102	Cams L35/45
c)	1-260	Hooked Cam
c)	1-261	Cam with Ramp
c)	1-262	Cam with or without ramp
c)	209-9002.00-00000	Sealing kit IP65
	200-0001.00-00000	Assembling cam without o-ring
f)	200-0002.00-00000	Assembling cam with o-ring
f)	6-100	Key
g)		

