



## 4-161SL Hinge Pr05 SNAP-LINE 180°



door bending 20mm, for surface mounted door, tool-less installation

### Benefits:

- ▶ 180° Hinge SNAP-LINE for surface mounted door for adjacent cabinets.
- ▶ RH or LH application.
- ▶ 180° also with adjacent doors/hinges.
- ▶ Closed cutout.
- ▶ Installation of the frame-part by simple push into the cutout.
- ▶ Water- and dust-tight according to IP65 DIN EN 60529 by using the O-ring (not included).

### Material:

- ▶ **Frame-part and door-part:** zinc die, black
- ▶ **Pin:** steel, zinc plated
- ▶ **Pivot pin:** steel, zinc plated
- ▶ **Washers:** brass, nickel plated
- ▶ **Snap wedges:** sintered metal, coated



## Hinge

	Part Number	Pin version	Clamping range (S)	Material Pin	Installation type
a)	412-9003.00-00015	loose	1.2 - 1.7	steel, zinc plated	Tool-less
a)	412-9003.00-00020	loose	1.7 - 2.2	steel, zinc plated	Tool-less
a)	412-9003.00-00025	loose	2.2 - 2.7	steel, zinc plated	Tool-less
a)	412-9003.00-00030	loose	2.7 - 3.2	steel, zinc plated	Tool-less

### Additional Information:

412-9003.00-00015, 412-9003.00-00020, 412-9003.00-00030 Water and dust-tight according to IP65 by using the O-ring 839-3770.00-02022

412-9003.00-00025 Water and dust-tight according to IP65 by using the O-ring 839-3771.00-00935 and flat external seal 200-0901

### Complementary Products:

	839-3770.00-02022	O-ring 20 x 2.2mm
b)	292-0401.00-03010	Cutout-cover
	292-0702.15-01030	Reinforcement plate for cutout SNAP-LINE
	292-0306.80-02530	Tool for uninstallation

