



4-182.05SL Hinge Pr05 SNAP-LINE 180°



door bending 25mm, for surface mounted door, for adjacent cabinets, frame-part and door-part snap-in, tool-less installation

Benefits:

- ▶ 180° Hinge SNAP-LINE.
- ▶ Lift-off.
- ▶ Installation of both door-part and frame-part by simple snap-in.
- ▶ RH and LH application.
- ▶ After retracting the pin-halves, the door can be pulled out horizontally at about 30° door opening.
- ▶ Special wire springs, fitted into the door-part, make the pin-halves captive and the pin-halves have a detent in both positions.
- ▶ Removing of the door please refer to product system 4-182.04SL.
- ▶ Uninstallation of the hinge please refer to product system 4-182SL.
- ▶ **Water- and dust-tight according to IP65 DIN EN 60529 by: O-ring 200-1005.00-02420.**

Material:

- ▶ **Frame-part, door-part and pin:** zinc die, black
- ▶ **Snap wedges:** sintered metal, coated
- ▶ **Detent spring:** spring steel



Hinge

Part Number	Clamping range (S)	Material Pin	Installation type
412-9020.00-00015	1.2 - 1.7	zinc die	Tool-less
412-9020.00-00020	1.7 - 2.2	zinc die	Tool-less
412-9020.00-00025	2.2 - 2.7	zinc die	Tool-less
412-9020.00-00030	2.7 - 3.2	zinc die	Tool-less
412-9020.00-00035	3.2 - 3.7	zinc die	Tool-less



Complementary Products:

200-1005.00-02420	O-ring 24x2.0
292-0402.00-03014	Cutout-cover
292-0701.15-01530	Reinforcement plate for cutout SNAP-LINE
292-0306.80-02530	Tool for uninstillation
292-0301.15-00000	Tool for uninstillation

