



4-184.05SL Hinge Pr05 SNAP-LINE 180°

Lift-off, door bending 25mm, for surface mounted door, frame-part screw-on, door-part snap-in

Benefits:

- 180° Hinge SNAP-LINE for adjacent cabinets.
- Door bending 25mm.
- Frame-part screw-on, steel version for heavy applications.
- Door-part snap-in.
- Lift-off.
- RH and LH version.
- To merge the door-part and the frame-part: at about 30° door opening, enter the door-part into the matching openings in the frame-part and close the door.
- Lift-off safety, the door can't be lifted off in closed position.
- The frame-part is fitted from outside by M6 countersunk screws.
- The installation of the door-part is achieved by a simple push into the appropriate cutout.
- The possible door-notch at the door (50mm) is concealed by the hinge (60mm).
- Other surfaces on request!

Material:

- **Door-part:** zinc die, black
- Frame-part:** steel, black
- Snap wedges:** sintered steel
- Pin:** stainless steel
- Spring:** spring steel
- Washer:** brass, nickel plated



Hinge, version RH

Part Number	Pin version	Material Pin	Clamping range frame-part (S)	Installation type
412-9016.00-00015	pressed in	stainless steel	1.3 - 2.0	Tool-less / screw-on
412-9016.00-00020	pressed in	stainless steel	1.8 - 2.5	Tool-less / screw-on
412-9016.00-00025	pressed in	stainless steel	2.3 - 3.0	Tool-less / screw-on
412-9016.00-00030	pressed in	stainless steel	2.8 - 3.5	Tool-less / screw-on

Hinge version LH

Part Number	Pin version	Material Pin	Clamping range frame-part (S)	Installation type
412-9017.00-00015	pressed in	stainless steel	1.3 - 2.0	Tool-less / screw-on
412-9017.00-00020	pressed in	stainless steel	1.8 - 2.5	Tool-less / screw-on
412-9017.00-00025	pressed in	stainless steel	2.3 - 3.0	Tool-less / screw-on
412-9017.00-00030	pressed in	stainless steel	2.8 - 3.5	Tool-less / screw-on

Complementary Products:

292-0702.15-01030

Reinforcement plate for cutout SNAP-LINE

292-0306.80-02530

Tool for uninstallation

