



## 6-162SL Compression Latch



Z-line lever actuated, flush

### Benefits:

- ▶ Clip-in, low profile compression latch for doors and panels with a sheet metal thickness of 1.4 to 3mm or, with a different housing, 3 to 3.4mm thickness.
- ▶ This latch is mainly designed for light duty applications: e.g. panels and hatches for vehicles as well as for electrical enclosures, A/C and air treatment enclosures (glove compartments, maintenance panels etc.).
- ▶ The completely pre-assembled latch is slid into the cutout in the open position and pushed-down into its final position.
- ▶ The design of the wide hook and the two clips guarantee a strong and solid fixation in the panel.
- ▶ The adjusting screw guarantees a consistent pressure to the seal and can be adjusted upon need.
- ▶ Weight: without lock 40g/1.43 oz with lock 55g/2 oz.

### Material:

- ▶ **Compression latch:** PA, black
- ▶ **Screw and nut:** steel, zinc plated
- ▶ **Spring:** stainless steel



## Compression Latch, non locking

Part Number	Installation type	Door thickness
282-9408.00-00000	tool-less	1,4 - 3 mm
282-9410.00-00000	tool-less	3 - 3,4 mm

## Compression Latch, lockable

Part Number	Closing	Installation type	Door thickness
282-9407.00-00000	DIRAK 1333	tool-less	1,4 - 3 mm
282-9409.00-00000	keyed different/mixed	tool-less	1,4 - 3 mm
282-9411.00-00000	DIRAK 1333	tool-less	3 - 3,4 mm
282-9412.00-00000	keyed different/mixed	tool-less	3 - 3,4 mm



Additional Information:

282-9407.00-00000, 282-9409.00-00000  
282-9411.00-00000, 282-9412.00-00000 With stainless dust-shutter

## Mounting instruction



