



7-075 Safety Quarter-Turn Pr20.1 L18

for cutout 20.1, length 18, vibration-proof, stainless steel AISI 316



Benefits:

- ▶ Safety Quarter-Turn, vibration-proof with high compression force.
- ▶ With the double bit versions the key is captive in the open position, according to DIN 43668.
- ▶ Water- and dust-tight according to IP65 DIN EN 60529.
- ▶ **Additional advantage:** completely closed surface.

Material:

- ▶ **Housing, insert, escutcheon and spring loaded link:** stainless steel AISI 316L



Quarter-turn with insert

	Part Number	Insert	Housing length	Door-thickness	Material	Surface	Installation type	Version
a)	255-9409.00-00000	Double bit 5mm pin	L18	max.8mm	stainless steel	stainless steel	screw-on	RH
a)	255-9410.00-00000	Double bit 5mm pin	L18	max.8mm	stainless steel	stainless steel	screw-on	LH
a)	255-9402.00-00000	Square 7mm	L18	max.8mm	stainless steel	stainless steel	screw-on	RH / LH
a)	255-9403.00-00000	Square 8mm	L18	max.8mm	stainless steel	stainless steel	screw-on	RH / LH
a)	255-9405.00-00000	Triangular 8mm	L18	max.8mm	stainless steel	stainless steel	screw-on	RH / LH
a)	255-9429.00-00000	Double bit 3mm pin	L18	max.8mm	stainless steel	stainless steel	screw-on	RH
a)	255-9430.00-00000	Double bit 3mm pin	L18	max.8mm	stainless steel	stainless steel	screw-on	LH



Additional Information:

255-9409.00-00000 as drawn

Complementary Products:

7-105

Cams L35/45

b) 1-262

Cam with or without ramp

b1) 200-0001.00-00000

Assembling cam without o-ring

c)

