



7-080 Quarter-Turn Pr20.1 L18 - L60

for cutout 20.1, length 18-60, stainless steel

Benefits:

- ▶ Quarter-Turn, RH or LH application.
- ▶ Water- and dust-tight according to IP65 DIN EN 60529.
- ▶ For IP67 use additional O-Ring 10x2mm.
- ▶ This Quarter-Turn consists of three basic parts which can be combined to suit your application.
- ▶ On request parts can be assembled by DIRAK.
- ▶ A pre-assembled Quarter-Turn can be installed in the cutout.

Material:

- ▶ **Housing:** stainless steel AISI 303 or AISI 316L
- ▶ **Insert:** stainless steel AISI 316L or PA
- ▶ **Cam:** stainless steel AISI 304
- ▶ **Grounding nut:** stainless steel AISI 316L
- ▶ **Adapter:** stainless steel AISI 316
- ▶ **Flat external seal and O-ring:** NBR



Quarter-turn

	Part Number	Housing length	Door-thickness	Material	Surface	Grounding type	Installation type	Version
a)	200-9043.00-00000	L18	max.8mm	stainless steel	stainless steel	Grounding nut	screw-on	AISI 316L
a)	200-9072.00-00000	L30	max. 20mm	stainless steel	stainless steel	Grounding nut	screw-on	AISI 303
a)	100-9024.00-00000	L36	max.26mm	stainless steel	stainless steel	Grounding nut	screw-on	AISI 303
a)	200-9073.00-00000	L40	max. 30mm	stainless steel	stainless steel	Grounding nut	screw-on	AISI 303
a)	200-9074.00-00000	L50	max.40mm	stainless steel	stainless steel	Grounding nut	screw-on	AISI 303
a)	200-9075.00-00000	L60	max.50mm	stainless steel	stainless steel	Grounding nut	screw-on	AISI 303



Additional Information:

200-9043.00-00000

Water and dust-tight according to IP67 DIN EN 60529 by using the O-ring 200-1002

Complementary Products:

	100-9019.00-00000	Adapter set L14
	100-9020.00-00000	Adapter set L21
	100-9021.00-00000	Adapter set L33
	100-9022.00-00000	Adapter set L33
	100-9023.00-00000	Adapter set for GI 60
	7-082	Insert stainless steel Pr20.1
	7-105	Cams L35/45
	6-100	Key
	1-270	Dust Caps and Sealing Plug Pr20.1
b)	1-270.01	Finger Pull for Quarter-Turn Pr20.1
c)	200-0002.00-00000	Assembling cam with o-ring

