



## 7-080.01 Quarter-Turn Pr20.1 L18



Elegant low profile Quarter-turn

### Benefits:

- ▶ RH / LH application.
- ▶ Please configure the Quarterturn with insert and cam.
- ▶ On request parts can be assembled.
- ▶ The Quarter-turn, stainlesssteel, can be screwed into the cutout with the preassembled cam.
- ▶ IP65 according to DIN EN 60529.
- ▶ IP67 according to DIN 60529 and IP69K according to DIN 40050 by: additional o-ring 200-1002.
- ▶ (S) = max. 8mm.

### Material:

- ▶ **Housing:** stainless steel AISI 316
- ▶ **Insert:** stainless steel AISI 316
- ▶ **Cams and serrated screw:** stainless steel AISI 304
- ▶ **O-Rings:** NBR
- ▶ **Grounding nut:** stainless steel AISI 316L



## Quarter-turn

	Part Number	Housing length	Door-thickness	Material	Surface	Grounding type	Installation type
a)	100-9601.00-00000	L18	max.8mm	stainless steel	stainless steel	Grounding nut	screw-on

### Complementary Products:

	7-082	Insert stainless steel Pr20.1
b)	6-100	Key
	7-105	Cams L35/45
c)	200-0002.00-00000	Assembling cam with o-ring
d)		

