



7-081.01 Quarter-Turn with Insert SW13 Pr20.1 L18



Quarter-turn with insert SW13 for hygienic applications

Benefits:

- ▶ Suitable for the food sector and hygienic areas.
- ▶ Meets hygiene requirements acc. to DIN EN ISO 14159 and DIN EN 1672-2.
- ▶ Polished surface.
- ▶ RH or LH application.
- ▶ Lockable with cylinder barrel.
- ▶ Seal FDA conform.
- ▶ IP65/67 DIN 60529 .
- ▶ Grounding by grounding nut.
- ▶ Cam can be delivered pre-assembled upon request.
- ▶ The pre-assembled Quarter-Turn can be installed in the cutout.

Material:

- ▶ **Housing, grounding nut and insert:** stainless steel AISI 316L
- ▶ **Cam and serrated screw:** stainless steel AISI 304
- ▶ **O-rings:** silicone, FDA conform, red or blue

1. = O-rings



Quarter-turn

| | Part Number | Insert | Housing length | Material | Surface | Grounding type | Installation type | Version |
|----|-------------------|--------|----------------|-----------------|-----------------|----------------|-------------------|-------------|
| a) | 100-9501.00-00001 | SW13 | L18 | stainless steel | stainless steel | Grounding nut | screw-on | blue o-ring |
| a) | 100-9501.00-00000 | SW13 | L18 | stainless steel | stainless steel | Grounding nut | screw-on | red o-ring |

Complementary Products:

| | | |
|----|-------------------|----------------------------|
| | 7-105 | Cams L35/45 |
| b) | 204-0140.00-00000 | Female key |
| c) | 200-0002.00-00000 | Assembling cam with o-ring |
| d) | | |

