



7-090 Quarter-Turn with T-Handle Pr20.1 L18

for cutout 20.1, length 18, stainless steel AISI 316

Benefits:

- Quarter-turn with T-handle.
- RH or LH application.
- Water- and dust-tight according to IP65 DIN EN 60529.
- The Quarter-turn consists of two basic components which can be combined to suit your application.
- On request parts can be assembled by DIRAK.
- **A pre-assembled Quarter-turn can be installed in the cutout.**

Material:

- **T-Handle:** completely AISI 316, surface polished
- **Nut and cam:** stainless steel



Quarter-turn with T-handle+fitting nut

	Part Number	Latching type	Closing	Housing length	Door-thickness	Material	Surface	Installation type
a)	200-9374.00-00000			L18	max.8mm	stainless steel	stainless steel	screw-on
a)	200-9398.00-00000	Cylinder	keyed alike DIRAK 1333	L18	max.8mm	stainless steel	stainless steel	screw-on
a)	200-9399.00-00000	Cylinder	keyed different	L18	max.8mm	stainless steel	stainless steel	screw-on

Complementary Products:

	7-105	Cams L35/45
b)	1-262	Cam with or without ramp
b)	200-0001.00-00000	Assembling cam without o-ring
c)	200-0019.00-00000	Assembling cam 90° to handle without o-ring
c)		

