



7-095.02 Quarter-Turn with T-Handle Pr20.1 L30/50

for cutout 20.1, lengths 30 and 50, stainless steel AISI 304



Benefits:

- ▶ Quarter-turn with T-handle with extended housing.
- ▶ Maximum door-thickness 20mm / 40mm.
- ▶ RH and LH application.
- ▶ Single sided grounding nut.
- ▶ Water- and dust-tight according to IP65 DIN EN 60529.
- ▶ Pre-assembled without cam.
- ▶ Further housing lengths on request.
- ▶ All lockable handles supplied with two keys.
- ▶ **Price and delivery time on request.**

Material:

- ▶ **Handle:** stainless steel AISI 304, satin polished
- ▶ **Housing, grounding nut and adapter:** stainless steel
- ▶ **Flat external seal:** NBR, black

Quarter-turn with T-handle

	Part Number	Latching type	Closing	Housing length	Door-thickness	Material	Surface	Grounding type	Installation type
a)	100-9401.00-00000			L30	max. 20mm	stainless steel	stainless steel	Grounding nut	screw-on
a)	100-9402.00-00000	Cylinder	keyed alike DIRAK 1333	L30	max. 20mm	stainless steel	stainless steel	Grounding nut	screw-on
a)	100-9403.00-00000	Cylinder	keyed different	L30	max. 20mm	stainless steel	stainless steel	Grounding nut	screw-on
a)	100-9404.00-00000			L50	max.40mm	stainless steel	stainless steel	Grounding nut	screw-on
a)	100-9405.00-00000	Cylinder	keyed alike DIRAK 1333	L50	max.40mm	stainless steel	stainless steel	Grounding nut	screw-on
a)	100-9406.00-00000	Cylinder	keyed different	L50	max.40mm	stainless steel	stainless steel	Grounding nut	screw-on

Complementary Products:

	7-105	Cams L35/45
b)	1-102	Cams L35/45
b)	1-262	Cam with or without ramp
b)	200-0001.00-00000	Assembling cam without o-ring
c)	200-0019.00-00000	Assembling cam 90° to handle without o-ring
c)		

