



# 4-394SL Pin Hinge Pr02 120°



### Advantages

- Concealed hinge with spring-loaded handle.
- Tool-less and quick assembly of the hinge.
- Tool-less assembly/ disassembly of the door.
- Flexible use for material thicknesses up to 4mm.
- Handle with grip area.
- Usable also as locking pin.
- Available with pin diameter of 6mm or 8mm.
- On request also available with another handle (see PS 6-211SL).

### Materials

- **Pin:** steel, zinc plated
- **Handle:** PA, green
- **Spacer:** PA, black

### Remarks

1. Assembled without tools by pressing the locking pin into the handle.
2. Disassembling the door.
3. Door installed.
4. By reducing the material in the cutout, the distance between the two components can be adjusted.



## Pin Hinge

|    | Part Number       | Pin diameter | Cutout pin    | Cutout housing | Clamping range | Packaging unit |
|----|-------------------|--------------|---------------|----------------|----------------|----------------|
| a) | 245-9312.00-00000 | 6,0 mm       | Ø 6.1 + 0.1mm | Ø 9.5 + 0.1 mm | 0,0 - 4,0 mm   | 50 pcs.        |
| b) | 245-9313.00-00000 | 8,0 mm       | Ø 8.1 + 0.1mm | Ø 9.5 + 0.1 mm | 0,0 - 4,0 mm   | 50 pcs.        |

