

6-167 Trigger Latch with compression 90 x 35

RoHS
WEEE

IP
66

Advantages

- Flat Trigger Latch with handle plate.
- Handle plate with release button.
- Including pre-assembled mounting bracket.
- Turning the screw from the outside spreads the mounting bracket and leads together with the specific housing design to a firm fixing.
- No need for assembly from the inside.
- No loose parts.
- In closed position the trigger latch cannot be disassembled.
- Easy adjustment of the H-dimension from 31 to 43mm (1.)
- Water- and dust-tight according to IP66 DIN EN 60529.
- Foamed sealing (captive).

Materials

- **Trigger Latch:** zinc die, black textured powder coated
- **Mounting bracket and screw:** steel, zinc plated

Remarks

1. = H-dimension
- Installation:
2. The complete trigger latch can be installed in the cutout from the front.
 3. By turning the screw (socket hex. SW3) from the outside, the mounting bracket spreads and fixes the latch in the door panel.
 4. The trigger latch is securely fastened by the mounting bracket in the cutout.
 5. By closing the latch the door is pulled against the frame.



Trigger Latch, lockable

Part Number	Latching type	variable H-dimension
353-2052.00-00001	keyed alike DIRAK 1333	31,0 - 43,0 mm

