R159 4 Km/h POLYAMIDE MONOLITHIC WHEEL WITH RIGID STEEL FORK WITH **BEARING (HEAVY DUTY)**

Materials:

Wheel body (1): Polyamide. Resistant to oils and greases. Tread (2): Polyamide. Resistant to oils and greases.

Surface finish: Smooth.

Colour: (1-2) Natural white. (3-4-5-6) Galvanised blue.

Wheel rotation (4): A pair of steel ball bearings is inserted to provide excellent rollability.

Bracket (3): Extra-thick steel (DD13) fork, with mounting holes in the base.

NEW

Wheel fastening (6): Steel hex head screw, coupled with a self-locking steel nut.

Special requests:

• Upon request and for a minimum of 20 pieces, the wheel can be supplied with a needle roller cage, (replace code no. R159 with code no. R149).





+80°


PA6

UL94

HB







| ` | art. | D | А | н | Е | G | М | N | с | h | ĝ | F1 (Kg) |
|----------|---------------------|-----|----|-----|-----|-----|-----|----|----|----|---|---------|
| • | R159100.T35P080X060 | 100 | 35 | 135 | 100 | 88 | 80 | 60 | 12 | 9 | - | 370 |
| • | R159125.T35P080X060 | 125 | 35 | 161 | 100 | 88 | 80 | 60 | 12 | 9 | - | 380 |
| • | R157125.T45P105X080 | 125 | 45 | 164 | 134 | 114 | 105 | 80 | 23 | 12 | - | 600 |
| • | R159150.T40P105X080 | 150 | 40 | 188 | 134 | 111 | 105 | 80 | 23 | 12 | - | 330 |
| • | R159150.T45P105X080 | 150 | 45 | 195 | 134 | 114 | 105 | 80 | 23 | 12 | - | 600 |
| • | R159200.T50P105X080 | 200 | 50 | 242 | 134 | 114 | 105 | 80 | 23 | 12 | - | 600 |



Stock availability as % (👿) 90% (●) - 40% (●) - 5% (●)