

R257

NEW



POLYAMIDE / POLYURETHANE WHEEL WITH RECTANGULAR SWIVEL PLATE AND STEEL BEARINGS (HEAVY DUTY SERIES)

Materials:

Wheel body (1):

Polyamide. Resistant to oils and greases.

Tread (2):

Injected polyurethane. Hardness 60 ± 5 Shore D.

Surface finish:

Smooth.

Colour:

(1) Natural white.

(2) Red (Ral 3013).

(3-4-5-6) Galvanised blue.

Wheel rotation (4):

A pair of steel ball bearings is inserted in the wheel hub to provide excellent rollability.

Bracket (3):

Extra-thick steel (DD13) fork.

Rotating assembly (5):


Steel rotating assembly with double ball race, assembled with steel screw grade 8.8 and rectangular swivel plate with four slotted mounting holes.

Wheel fastening (6):

Steel hex head screw, coupled with a self-locking steel nut.

Special requests:

- Upon request and for a minimum of 20 pieces, the wheel can be supplied with a needle roller cage, (replace code no. R257 with code no. R247).



| | art. | D | A | H | I | E | G | M | N | c | h | g | F1 (Kg) |
|---|---------------------|-----|----|-----|----|-----|-----|-----|----|----|----|---|---------|
| ● | R257080.T34P080X060 | 80 | 34 | 125 | 47 | 100 | 84 | 80 | 60 | 12 | 9 | - | 260 |
| ● | R257100.T40P080X060 | 100 | 40 | 135 | 47 | 100 | 84 | 80 | 60 | 12 | 9 | - | 300 |
| ● | R257125.T40P080X060 | 125 | 40 | 161 | 51 | 100 | 84 | 80 | 60 | 12 | 9 | - | 400 |
| ● | R257150.T45P105X080 | 150 | 45 | 195 | 60 | 132 | 110 | 105 | 80 | 23 | 12 | - | 600 |
| ● | R257200.T50P105X080 | 200 | 50 | 242 | 59 | 132 | 110 | 105 | 80 | 23 | 12 | - | 700 |