WELDABLE BLACK-OXIDE TREATED STEEL KNOB STYLE INDEXING PLUNGER WITH PIN



Material:

(4) Reinforced polyamide scallop knob.

Inserts:

- (3) Zinc plated steel spring.
- (2) Bored unthreaded, welding quality steel body.
- (1) Hardened hight resistance steel plunger pin.
- **ATTENTION:** The manufacturer recommends making the lodging hole for the plunger pin with a tolerance H7.

Surface: (4) Black satin finish (RAL 9011). (1.2) Black-oxide finish.

Packs containing 10 pieces.


SPECIAL REQUESTS:


• On request and for special quantities the knob is avaiable in a choice of colours as indicated in the table on page 31.


ATTENTION:


TO AVOID PROBLEMS WHEN WELDING THE IRON BODY TO THE MACHINERY, THE PLASTIC KNOB IS SUPPLIED SEPARATELY. SCREW THE KNOB ON ONCE THE PART HAS COOLED.











Plunger in retracted position

~~~	Art.	D	Н	h	d2	d	d1-0,02	Q	۵۵ g
$\odot$	W806.Q0501	22	45	22	12	12	5	5	23
$\overline{\mathbf{S}}$	W806.Q0601	27	54	26	14	14	6	6	40
$\overline{\otimes}$	W806.Q0801	33	68	34	18	19	8	8	84

Presumable presence in the stock in % () 90%(☺) 40%(☺) 5%(☺)) BOTECO ® - © All right reserved - www.boteco.it Any unathorized reproduction is strictly forbidden

FALLIN W-S-3

BOTECO

METAL

