



Elegant, low profile Quarter-Turn, vibration-proof also **at high sealing pressure** through an integrated latch. Especially narrow design, cutout 32x20,1mm.

- Operation not possible without an appropriate key.
- The key is captive in open position according to DIN 43668.
- **Additional advantage:** complete closed surface.
- Pre-assembled Quarter-Turn can easily be snapped-in.
- No tools needed.
- Vibration-proofed fixing.
- Blind installation.
- Rectangular cutout guarantees a perfect alignment.
- 90° cam rotation.
- LH and RH application.
- Pre-assembling of cam on request.
- Water- and dust-tight according to IP65.
- Grounding/earthing see f).

Attention: H-dimension of the cam $\geq 12\text{mm}$ (0.472)!

Material:

- **Housing, Insert, Spring loaded link and Escutcheon:** zinc die, chrome plated
- **Snap wedges:** sintered steel
- **Spring:** spring steel
- **O-Ring:** NBR/ Perbunan 70° +/-5° Shore, black
- **Serrated screw:** steel, zinc plated

	clamping range (s)	Part-No.
a) Safety Quarter-Turn	1.0 - 1.7	455-9001.00-00013
with insert double bit 3 pin	1.5 - 2.2	455-9001.00-00018
	2.3 - 3.0	455-9001.00-00026
b) Safety Quarter-Turn	1.0 - 1.7	455-9002.00-00013
with insert double bit 5 pin	1.5 - 2.2	455-9002.00-00018
	2.3 - 3.0	455-9002.00-00026
c) Safety Quarter-Turn	1.0 - 1.7	455-9004.00-00013
with insert square 8	1.5 - 2.2	455-9004.00-00018
	2.3 - 3.0	455-9004.00-00026

Other (s) - dimensions on request!

d) Cams see product system 1-095, 1-100, 1-262, 7-080 and 7-105

e) 3-point cam see product system 1-100 and 2-151

f) Grounding/ Earthing clip (not shown) **200-1101.04-00000**

g) Please contact DIRAK for the Part-No. of a completely pre-assembled SNAP-LINE Quarter-Turn.

12/15/08

© copyright by DIRAK / Germany