



Cylinder Quarter-Turn with 90° rotation, RH or LH application.

- Double insulated and vibration-proof.
- The Quarter-Turn consists of two basic components which can be combined to suit your application.
- On request cam can be assembled by DIRAK.
- A pre-assembled Quarter-Turn can be installed in the cutout.

**Material:**

- a)
  - **Housing:** PA, black
- b)
  - **Cam:** PA, black
- d)
  - **Finger pull:** PA, black

a) Housing with tumbler barrel	keyed alike	keyed
<b>(Head Ø28) with:</b>	<b>DIRAK 1333</b>	<b>different/mixed</b>
fixing-nut PA (black)	<b>200-9210</b>	<b>200-9213</b>
fixing-nut steel (zinc plated)	<b>200-9211</b>	<b>200-9214</b>
fixing-nut stainless steel	<b>200-9212</b>	<b>200-9215</b>

b) Cam PA (black)	H in mm / inch *	
	18 / 0.709	<b>200-5318</b>
	20 / 0.787	<b>200-5320</b>
	22 / 0.866	<b>200-5322</b>
	25 / 0.984	<b>200-5325</b>
	28 / 1.102	<b>200-5328</b>

b1) Cam steel (zinc plated) see product system 1-100 or 1-262

**Optional:**

Water- and dust-tight according to IP65, DIN 40050, by:

c) **Dustcaps** see product system 1-270

d) **Finger pull** see product system 1-270 for example **200-4703.3**

e) **Assembling of cam** **200-0001**

**All locks supplied with 2 keys.**

\* Special cams on request.