



2-110 Swinghandle RS 130 for Rod Latch PrA



for cutout 130, for rod latch FS and round rods

Benefits:

- ▶ Flush mounted Swinghandle for sheet metal and plastic enclosures. The Swinghandle has a 90° rotation
- ▶ RH or LH application.
- ▶ The polyamide handle is fully insulated.
- ▶ The Swinghandle can be locked with 40mm long profile-cylinders (DIN 18252).
- ▶ Water- and dust-tight according to IP65 DIN EN 60529.
- ▶ Rod latch requires lock support c) in figure below.
- ▶ For doors to be symmetrical for RH and LH operations, two squared cutouts 46mm with lock support cap c1) (in figure below) are required.

Material:

- a), a1), a2), a3) and a4)
 - ▶ **Swinghandle:** see table
- b) and b1)
 - ▶ **Rod Latch:** zinc die as well as steel, zinc plated
- c)
 - ▶ **Lock support:** zinc die
- d) and d1)
 - ▶ **Adapter:** zinc die
- e)
 - ▶ **Round rods:** steel, zinc plated



Swinghandle PA, black, for profile-cylinder, Ø46

	Part Number	Latching type	Internal cover	Cylinder cover	Sealable	Installation type
a)	207-9023.00-00000	PHZ 40mm	Ø46			screw-on
a1)	207-9024.00-00000	PHZ 40mm	Ø46	PA	Yes	screw-on
a2)	207-9030.00-00000	PHZ 45mm	Ø46	PA	Yes	screw-on

Swinghandle, handle zinc die, dish PA black, for profile-cylinder, Ø46

	Part Number	Latching type	Internal cover	Cylinder cover	Sealable	Installation type
a3)	207-9034.00-00000	PHZ 45mm	Ø46	PA	Yes	screw-on

Swinghandle, handle zinc die, dish PA black, for profile-cylinder, 46

	Part Number	Latching type	Rainforced dustcover	Internal cover	Cylinder cover	Sealable	Installation type
a4)	207-9346.00-00000	PHZ 45mm	Yes	46	PA	Yes	screw-on

Complementary Products:

b)	208-9001.00-00000	Rod latch
b1)	208-9008.00-00000	Rod latch
c)	207-3501.00-00000	Lock support Ø46
c1)	207-2706.00-00000	Lock support 46
d)	1-181SL	Adapter PA for Round Rods SNAP-LINE
d)	1-181.01	Adapter for Round Rods
e)	1-170	Round Rods
e)	201-0111.00-Lxxmm	Round rod, variable length
e)	201-0112.00-Lxxmm	Round rod, variable length
e)	201-9020.00-Lxxmm	Round rod, variable length
e)	201-9021.00-Lxxmm	Round rod, variable length
f)	1-190	Rod Guides for 8mm Round Rods
f)	1-193SL	Rod Guide RS SNAP-LINE
g)	2-140	Profile-Cylinder
h)	2-340.01	Rod Latch RS



