



4-249.04SL Hinge Pr01 SNAP-LINE 180°



for nested door

Benefits:

- ▶ Small elegant hinge.
- ▶ 180° Opening angle.
- ▶ To be mounted by simple pushing into appropriate cutouts and by screws.
- ▶ With the screw fastened versions countersunk screws according DIN 7991 or according DIN EN ISO 10642 can be used.
- ▶ Adjustments are possible with respective bores provided.
- ▶ The nut plate can be mounted in different ways, according to the application. (Please order separately)
- ▶ Countersunk screws are not included!

Material:

- ▶ **Hinge parts:** zinc die, matt chrome plated or matt black
- ▶ **Pin:** stainless steel
- ▶ **Snap wedges:** sintered steel, zinc plated
- ▶ **Nut plate:** steel, zinc plated



Hinge, zinc die, black

Part Number	Pin version	Clamping range (S)	Material Pin	Installation type
418-9304.33-00008	pressed in	0.6 - 0.9	stainless steel	Tool-less / screw-on
418-9304.33-00010	pressed in	0.8 - 1.1	stainless steel	Tool-less / screw-on
418-9304.33-00014	pressed in	1.2 - 1.5	stainless steel	Tool-less / screw-on
418-9304.33-00020	pressed in	1.8 - 2.1	stainless steel	Tool-less / screw-on
418-9304.33-00024	pressed in	2.2 - 2.5	stainless steel	Tool-less / screw-on

Hinge, zinc die, chrome plated

Part Number	Pin version	Clamping range (S)	Material Pin	Installation type
418-9304.40-00008	pressed in	0.6 - 0.9	stainless steel	Tool-less / screw-on
418-9304.40-00010	pressed in	0.8 - 1.1	stainless steel	Tool-less / screw-on
418-9304.40-00014	pressed in	1.2 - 1.5	stainless steel	Tool-less / screw-on
418-9304.40-00020	pressed in	1.8 - 2.1	stainless steel	Tool-less / screw-on
418-9304.40-00024	pressed in	2.2 - 2.5	stainless steel	Tool-less / screw-on

Complementary Products:

218-0907.15-00000

292-0306.80-02530

Tool for uninstallation

