



4-271SL Hinge Pr01 SNAP-LINE 180°

adjustable, for nested door

Benefits:

- ▶ Hinge 180° SNAP-LINE
- ▶ **Combination:** The first hinge half with D-SNAP-technology, the second hinge half can be adjusted (see drawing).
- ▶ 180° Opening angle.
- ▶ RH or LH application.
- ▶ The teeth on the adjusting bushings and in the oblong holes of the second hinge half prevent slipping of the hinge.
- ▶ In contrast with conventional oblong holes, the countersunk heads of the screws have full contact with the adjusting bushings.
- ▶ These bushings completely cover the oblong holes, preventing deposit of dust within the adjusting area.
- ▶ Matching arrow tips mark the 0-position.

Material:

- ▶ **Hinge halves:** zinc die, black
- ▶ **Adjusting bushings:** zinc die, black
- ▶ **Pin:** stainless steel
- ▶ **Snap wedges:** sintered steel



Hinge

	Part Number	Pin version	Clamping range (S)	Material Pin	adjustment direction	Installation type
A	418-9206.00-00020	pressed in	1.7 - 2.2	stainless steel	Width	Tool-less / screw-on
A	418-9206.00-00025	pressed in	2.2 - 2.7	stainless steel	Width	Tool-less / screw-on
A	418-9206.00-00035	pressed in	3.2 - 3.7	stainless steel	Width	Tool-less / screw-on
A	418-9206.00-00030	pressed in	2.7 - 3.2	stainless steel	Width	Tool-less / screw-on
B	418-9207.00-00020	pressed in	1.7 - 2.2	stainless steel	Height	Tool-less / screw-on
B	418-9207.00-00025	pressed in	2.2 - 2.7	stainless steel	Height	Tool-less / screw-on
B	418-9207.00-00030	pressed in	2.7 - 3.2	stainless steel	Height	Tool-less / screw-on
B	418-9207.00-00035	pressed in	3.2 - 3.7	stainless steel	Height	Tool-less / screw-on

Complementary Products:

6-041	Countersunk screws and Hexagon nuts
292-0701.15-01530	Reinforcement plate for cutout SNAP-LINE
292-0306.80-02530	Tool for uninstallation
292-0301.15-00000	Tool for uninstallation

