



6-1381 Flush Mounted Trap-Door Latch



with integrated T-handle and safety insert, zinc die

Benefits:

- Flush mounted trap-door latch with integrated T-handle and safety insert.
- Can be used in any position.
- Vibration-proof design.
- T-handle with 95° opening angle.
- Width of T-handle 25mm (0.984).
- T-handle locked when closed.
- T-handle with rubber stop to prevent rattling.
- Encasement surface perfectly smooth to prevent dirt deposits.
- Mounted with fastening bracket with two M6 allen screws DIN EN ISO 4762.
- Cutout with anti-twist safeguard.
- Also available without locking device (only flush-mounted T-handle).
- The door strength amounts to max. Ts=6mm (0.236) with the screw provided M6x16 .
- **Attention:** H-dimension of the L=35 cam =14mm
H-dimension of the L=45 cam =14mm
- Only for use with cams part-no. 200-06XX und 200-04XX!

Material:

- **Housing and T-handle:** zinc die, chrome plated
- a)
- **Insert:** zinc die, chrome plated
- a2)
- **Insert:** stainless steel AISI 303



trap-door latch

	Part Number	Insert	Installation type	Version
a)	213-9402.00-00000	Square 8mm	screw-on	with Fixing bracket
a1)	213-9401.00-00000	Non locking	screw-on	without Fixing bracket
a2)	213-9403.00-00000	Conical Square 9mm	screw-on	without Fixing bracket



Additional Information:

213-9402.00-00000	With fastening bracket
213-9401.00-00000	Without fastening bracket
213-9403.00-00000	Without fastening bracket Special version: without locking device and without cam connection

Complementary Products:

1-102	Cams L35/45
204-0103.00-00000	Female key
204-0701.07-07500	Universal rail key
6-1381	Key

Operation



