



7-103 Quarter-Turn with L-Handle Pr20.1 L18

for cutout 20.1, length 18, stainless steel AISI 316

Benefits:

- Quarter-turn with L-handle.
- RH or LH application.
- Water- and dust-tight according to IP65 DIN EN 60529.
- The Quarter-Turn consists of two basic components which can be combined to suit your application.
- On request parts can be assembled by DIRAK.
- A pre-assembled Quarter-Turn can be installed in the cutout.
- All lockable handles supplied with two keys.
- **Price and delivery time on request.**

Material:

- **L-handle:** completely stainless steel AISI 316, surface polished
- **Nut and cam:** stainless steel



Quarter-turn with L-handle

	Part Number	Latching type	Closing	Housing length	Door-thickness	Material	Surface	Installation type
a)	200-9418.00-00000			L18	max.8mm	stainless steel	stainless steel	screw-on
a)	200-9485.00-00000	Cylinder	keyed alike DIRAK 1333	L18	max.8mm	stainless steel	stainless steel	screw-on
a)	200-9486.00-00000	Cylinder	keyed different	L18	max.8mm	stainless steel	stainless steel	screw-on

Complementary Products:

	7-105	Cams L35/45
b)	1-102	Cams L35/45
b)	1-262	Cam with or without ramp
b)	200-0001.00-00000	Assembling cam without o-ring
c)	200-0019.00-00000	Assembling cam 90° to handle without o-ring
c)	200-0020.00-00000	Assembling cam, LH door
c)		

