

7-140 Concealed Hinge Pr03 120°



Advantages

- For surface mounted doors.
- Hinge concealed.
- Door bending 18 mm.
- RH / LH application.
- 120° Opening angle.
- Frame-part weld-on or screw-on.

Materials

- **Hinge parts: stainless steel AISI 304 or AISI 316L**
- **Pins: stainless steel AISI 303 or 316L**



Concealed Hinge

	Part Number	Material hinge-part	Material pin	Pin version	Installation type
a)	216-9101.00-00000	stainless steel AISI 304	stainless steel AISI 303	without groove	screw-on
b)	216-9109.00-00000	stainless steel AISI 304	stainless steel AISI 303	with groove incl. retaining ring	screw-on
c)	216-9109.00-00001	stainless steel AISI 304	stainless steel AISI 303	with groove incl. o-ring	screw-on
d)	216-9102.00-00000	stainless steel AISI 304	stainless steel AISI 303	without groove	screw- / weld-on
e)	216-9110.00-00000	stainless steel AISI 304	stainless steel AISI 303	with groove incl. retaining ring	screw- / weld-on
f)	216-9110.00-00001	stainless steel AISI 304	stainless steel AISI 303	with groove incl. o-ring	screw- / weld-on
f)	216-9121.00-00001	stainless steel AISI 316L	stainless steel AISI 316L	with groove incl. o-ring	screw- / weld-on
g)	216-9121.00-00002	stainless steel AISI 316L	stainless steel AISI 316L	with groove incl. retaining ring	screw- / weld-on

