

4-392 Pin Hinge Pr02 120°



Advantages

- Lift-off.
- For nested doors.
- Version LH/ RH.
- With springloaded pin for extension of the door.
- Versions Ø5mm are just welded-on.
- Versions Ø4mm and Ø6mm are welded-on and screwed-on.
- 120° opening angle.

Materials

- **Door-part:** steel, untreated or steel, zinc plated
- **Pin:** steel, zinc plated
- **Spring:** stainless steel



Pin Hinge, version RH (as drawn)

	Part Number	Door-part	Installation type	Pin length L	Ø Pin d	Material pin
a)	245-9001.00-00000		screw- / weld-on	58,0 mm	4,0 mm	steel, zinc plated
b)	245-9103.00-00000		screw-on	82,0 mm	5,0 mm	steel, zinc plated
c)	245-9113.00-00000	untreated	screw-on	82,0 mm	6,0 mm	steel, zinc plated
d)	245-9101.00-00000	untreated	screw- / weld-on	82,0 mm	6,0 mm	steel, zinc plated
d1)	245-9107.00-00000	zinc plated	screw- / weld-on	82,0 mm	6,0 mm	steel, zinc plated

Pin Hinge, version LH (mirror inverted)

	Part Number	Door-part	Installation type	Pin length L	Ø Pin d	Material pin
a)	245-9002.00-00000		screw- / weld-on	58,0 mm	4,0 mm	steel, zinc plated
b)	245-9104.00-00000		screw-on	82,0 mm	5,0 mm	steel, zinc plated
d)	245-9102.00-00000	untreated	screw- / weld-on	82,0 mm	6,0 mm	steel, zinc plated
d1)	245-9108.00-00000	zinc plated	screw- / weld-on	82,0 mm	6,0 mm	steel, zinc plated

Pin Hinge, not assembled

	Part Number	Door-part	Installation type	Ø Pin d	Material pin	Pin length L
b)	245-9105.00-00000		screw-on	5,0 mm	steel, zinc plated	82,0 mm
d)	245-9106.00-00000	untreated	screw- / weld-on	6,0 mm	steel, zinc plated	82,0 mm
d1)	245-9109.00-00000	zinc plated	screw- / weld-on	6,0 mm	steel, zinc plated	82,0 mm

